

AP-1[®]

HIGH TEMPERATURE MULTIPURPOSE GREASE

DESCRIPTION

AP-1 is based on bentone clay for high temperature tolerance and is non melting. AP-1 is rated to 288°C but does not thicken excessively at temperatures down to -18°C. It has mechanical stability, water resistance, excellent adhesion to metals, prevents wear and has superior storage life.

AP-1 contains oxidation inhibitors, corrosion inhibitors and metal deactivators. It offers positive protection for extreme services, which require heavy duty lubricant performance.

AP-1 is recommended for anti-friction bearings, ball and roller bearings, sleeve bearings, journals, shackles, slides, conveyor chains, universal joints, sealed assemblies, chassis and general lubrication.

ADVANTAGES

- Protects against rust and corrosion
- Prevents wear
- Highly adhesive to metal
- Resistant to water
- Superior storage life
- Colour Clear Amber
- No dropping point

APPLICATIONS

AP-1 is ideal for general purpose lubrication of plain and anti-friction bearings such as bearings in cookers, oven chain drives, forges, hot air blowers and dryers.

PRODUCT CHARACTERISTICS

Service range	-18°C to 288°	°C (0 to 500°F)		
Fluid Type		Petroleum		
Colour		Amber		
Dropping Point (ASTM D-566)		None		
Specific Gravity		0.91		
Additive Type		Organic		
Flash Point (ASTM D-92)		293°C (560°F)		
Autoignition Point (CALCULATED)		D) 360°C (680°F)		
NLGI Grade		2		
Penetration @ 2	(IP			
50/ASTM D-217)		265-295		
Copper Strip Corrosion		1A		
(ASTM D-4048)				
Shell 4-Ball (ASTM D-2596)				
Weld Point, k	<gf< td=""><td>160</td></gf<>	160		
Load Wear Index		25		
Wear Scar Diameter		0.65		
(ASTM D-2266)				
Base Oil Viscosity (ASTM D-445)				
cSt @ 40	°C	90-110		

PACKAGING

Code No.	Size	Container
JA31550	30 x 400g	Cartridge
JA31506	12 x 500g	Tub
JA31523	5kg	Pail
JA31516	16kg	Pail
JA31529	180kg	Barrel

LIMITED WARRANTY

Jet-Lube (UK) Limited makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube (UK) Limited materials and workmanship. This limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube (UK) Limited. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube (UK) Limited shall not be liable for incidental or consequential damages May 2013