EZY-TURN® #22

GATE VALVE SEAT SEALANT & BODY FILLER LUBRICANT

DESCRIPTION

EZY-TURN® #22 is a premium sealant formulated from a unique blend of synthetic and vegetable-based oils for use in expanding gate type valves. The ideal sealant for service applications involving gases, distillates, dilute acids, and steam. **EZY-TURN #22** contains no solid fillers that could disrupt the sealing film. Although designed for expanding gate-type valves, **EZY-TURN #22** is used effectively on many other valve types.

- Nontoxic
- Nonhazardous
- No Solid Fillers
- Reduces Torque
- Seals, Lubricates
- Vegetable & Synthetic Base
- Water resistant
- Multi-Purpose
- Hydrocarbon Resistant
- Pumpable

APPLICATIONS

Oilfield: EZY-TURN #22 has been formulated for use in production oilfield situations (Christmas trees, line valves) where a variety of service conditions may be required. This is a premium product and should be used where solid fillers mandated in the "peanut butter" type sealants are not wanted. **Industrial and Marine: EZY-TURN #22** is also recommended for gate valve applications requiring resistance to hydrocarbon or hydrocarbon/water mixtures. Absence of solid fillers assures that the service will not be contaminated with unwanted solids.

SERVICE RECOMMENDATIONS

- Petroleum Gases
- Petroleum Liquids
- Natural Gas
- Crude Distillates
- Dilute Alkalis
- Aqueous Solutions
- Butane
- Propane
- LPG
- Crude Oil
- Dilute Acids
- Salt Solutions

PRODUCT CHARACTERISTICS

Appearance	
Bulk & Stick	Amber Sticky Paste or Semi-Plastic
Penetration (ASTM D-217)	
Bulk	255 – 285
Stick	80 - 130
Density (lb/gal), Typical	
Bulk	8.72
Stick	8.94
Specific Gravity, Typical	
Bulk	1.04
Stick	1.07
Dropping Point (ASTM D-2265)	
Bulk & Stick	None
Oil Separation (FTMS 791.B M.321.2) (ASTM D-6184)	
Bulk	5.0 max
Stick	1.0 max
Thickener	
Bulk & Stick	Inorganic
Temperature Range	
Bulk & Stick	-50°F (-46°C) to 420°F (215°C)

Note: Not for use with oxygen or strong oxidizers.

For package types and part numbers contact sales@jetlube.com***.***

LIMITED WARRANTY

For warranty information please visit
http://www.jetlube.com/pdf/Jet-Lube_Warranty.pdf

You can also email us at sales@jetlube.com or write to the Sales Department at the address below.