

TOP GUN™ WASP & HORNET KILLER

DESCRIPTION

TOP GUN™ Wasp & Hornet Killer's new and improved formula is ozone friendly and still eliminates wasps, hornets, yellow jackets and bees on contact. This powerful new TOP GUN formula still provides instant knockdown on contact and leaves a residual that prevents area infestation. Instant knockdown is accomplished when the fast evaporating "inert" fluid freezes the stinging insect while at the same time dewaxing its wings. The slowly evaporating hydrocarbon fluid clogs the insects breathing ports causing it to suffocate. Finally, the synthetic pyrethrins provide the residual poison to kill the nest. JET-LUBE® trigger nozzle allows fast, accurate, dense jet stream delivery from up to 15 feet for safe application in hard to reach places. TOP GUN is EPA approved and has a dielectric strength of 35,000 volts. **Prior to use read all the precautionary and application instructions on the label.**

- Instant knockdown
- Kills on contact
- Accurate application
- Nonconductive
- 35 KV dielectric strength
- Indoor/Outdoor use
- EPA Reg. No. 44446-54-64169
- Ozone Friendly
- Nonflammable (CSMA Flame Projection Test)

APPLICATIONS

Use TOP GUN Wasp & Hornet Killer on wasps, hornets, yellow jackets and bees on HVAC equipment and enclosures, traffic signs, trees, cable television equipment, telecommunications equipment, telephone and utility poles, in attics and under eaves, transformers, electrical and water towers—any place with infestation.

PRODUCT CHARACTERISTICS

| | |
|--|---------------------------------|
| Spray Pattern—Typical | 4 Inch Diameter Stream @ 10 ft. |
| Propellant | HFC |
| Solvent Type | Hydrocarbon |
| Pyrethrins, Wt. % | 0.325 |
| Specific Gravity | 0.81* |
| Density (lb/gal) | 6.75 |
| Flash Point (ASTM D-92) | >145°F (63°C) |
| Dielectric Strength & Breakdown Voltage (ASTM D-877) | 35 KV, Typical |

* Without Propellant

ACTIVE INGREDIENTS:

| | |
|---|---------|
| Tetramethrin (1-Cyclohexene-1, 2-dicarboximido) methyl 2, 2-dimethyl-3-(2-methylpropenyl) cyclopropanecarboxylate | 0.200% |
| 3-Phenoxybenzyl-(1RS, 3RS; 1RS, 3RS)-2,2-dimethyl-3-(2-methylprop-1-enyl) cyclopropanecarboxylate..... | 0.125% |
| INERT INGREDIENTS: | 99.675% |

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT CALL CHEMTREC-DAY OR NIGHT-AT 1-800-424-9300

PACKAGING

| Code No. | Container Size | Container |
|----------|----------------|-----------|
| 51541 | 12 oz. | Aerosol |

LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.

CORPORATE LOCATIONS

Houston, Texas—World Headquarters

Maidenhead, England

Edmonton, Canada

JET-LUBE, INC.
4849 HOMESTEAD RD.,
P.O. BOX 21258 (77226-1258)
HOUSTON, TX 77028

WATS: 800-538-5823
PHONE: 713-674-7617
FAX: 713-678-4604
E-MAIL: sales@jetlube.com
www.jetlube.com

INDUSTRIAL

INDUSTRIAL

INDUSTRIAL

INDUSTRIAL

INDUSTRIAL