769 LUBRICANT®

PENETRANT AND LUBRICANT

DESCRIPTION

769 LUBRICANT® is the foremost penetrating, moisture displacing, lubricating and corrosion preventative available today. Unequalled where salt water, salt spray, or other harsh environments are encountered. **769 LUBRICANT®** gives total performance while being environmentally safe, easy to use and nonflammable.

Lubricates: Contains ashless extreme pressure additives and highly refined lubricating oils that provide superior lubricating protection and anti-wear properties.

Penetrates: Rusted and frozen metal parts - studs, nuts, screws, pins, linkages - are easily loosened by means of superior "creepability."

Removes Moisture: Moisture is lifted and displaced rather than trapped. Pores and crevices of surfaces are freed from moisture and are coated with a thin nongreasy film that prevents additional moisture from clinging or entering.

Prevents Rust & Corrosion: A thin film adheres to metallic surfaces, providing positive, temporary protection against the formation of rust and corrosion, including electrolytic and galvanic corrosion common in salt environments.

ADVANTAGES

- Nonflammable
- Economical to use
- Nonevaporating
- Contains no silicones
- Light machine oil base
- Never hardens or dries out

APPLICATIONS

Industrial: May be used to free rusted or corroded fasteners on pumps, turbines, heat exchangers, reactors, manholes, electric motors, or any industrial equipment that operates in high humidity or salt exposure environments, such as those found in paper mills, refineries, petrochemical plants and shipyards. Marine: Winches, shackle pins, toggle pins, pelican hooks, sheaves, swivels, capstans, digs, locks and door hinges, it dries out distributors, wiring harnesses, spark plugs, igniters and other ignition system parts. May be used on screws, nuts, bolts, studs, or any other fastener used to assemble marine equipment that is prone to rust or corrosion. Prevents saltwater corrosion of outboard motors. Excellent lubricant/preservative for nylon rope.

Automotive: Dries out wet ignition systems. May be used on door hinges, truck latches, door locks, exhaust systems or any nut, bolt, screw or fastener that is prone to "heat-freeze." Ideal for use on parts that are rusted or corroded as a result of exposure to road deicing salts.

Residential: For use throughout the home wherever a premium penetrating lubricant is desirable such as locks, chains, bikes, firearms, radio controlled vehicles, etc. On firearms, **769 LUBRICANT®** is an excellent bore and barrel cleaner and preservative and doubles as an excellent lubricant to prevent freeze-up.

CONFORMS TO:

Chacific Cravity

MIL-C-81309G (Aerosol) Type II & III, Class II, $\rm CO_2$ MIL-C-16173E Grade 3 CID A-A-50493C Class B Type II NSF H-2 Registered

PRODUCT CHARACTERISTICS

000

Specific Gravity	0.83
Color/Appearance	Clear Amber Fluid
Flash Point, Tag Close Cup	>81°C (177°F)
(ASTM D-56)	
Viscosity, Kinematic 40°C, cSt	4.5 - 8.5
(ASTM D-445)	
Pour Point (ASTM D-97)	-32°C (-25°F)
Dielectric Strength & Breakdown	
Voltage (ASTM D-877)	35 - 40 kv (typ.)
Vapor Pressure, mm Hg	0.4
@ 68°F	
рН	Neutral
Humidity Test	Passed
Rust Test (ASTM D-665)	Pass
Water, Wt%	None
Copper Strip Corrosion	IA
(ASTM D-130)	
NFPA 30B Storage Class	Level III

PACKAGING

Code No.	Size	Container
JA27534	5 litre	Metal Can
JA27529	189 litre	Drum

LIMITED WARRANTY

Jet-Lube (UK) Ltd makes the Limited Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube (UK) Ltd materials and workmanship.

This Limited Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube (UK) Ltd

The sole remedy for breach of the Limited Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube (UK) Ltd shall not be liable for incidental or consequential damages.



